




6A05 THRU 6A10

General Purpose Rectifier Diode

Reverse Voltage : 50~1000 Volts Foward Current : 6.0 Ampere

Features

- High surge current capability
- Plastic package has Underwriters Laboratory Flammability Classification 94V-O utilizing Flame Retardant Epoxy Molding Compound
- Void-free Plastic in a R-6 package
- High current operation 6.0 ampere at $T_A=60^{\circ}\text{C}$
- Exceeds environmental standards of MIL-S-19500/228



Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Parameter		Symbol	6A05	6A1	6A2	6A4	6A6	6A8	6A10	Unit
Maximum Recurrent Peak Reverse Voltage		V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage		V _{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage		V _{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current .342”(9.5mm) Lead Length at T _A =60°C		I _(AV)	6.0							A
Peak Forward Surge Current, 8.3ms Single Half-sine-wave Superimposed On Rated Load(JEDEC Method)		I _{FSM}	400							A
Maximum Forward Voltage at 6.0A DC and 25°C		V _F	1.1							V
Maximum Reverse Current At Rated DC Blocking Voltage	T _A =25°C	I _R	10.0							uA
	T _A =100°C		100							
Typical Junction Capacitance ⁽¹⁾		C _J	150							pF
Typical Thermal Resistance ⁽²⁾		R _{θJA}	10							°C
Operating Junction Temperature Range		T _J	-55~+150							°C
Storage Temperature Range		T _{STG}	-55~+150							°C

Notes:

1. Measured at 1 MHz and applied reverse voltage of 4.0 VDC.

2. Thermal Resistance From Junction to Ambient 0.375"(9.5mm) lead length P.C.B. Mounted with 1.1x1.1" (30x30mm) copper pads



6A05 THRU 6A10

Typical Characteristics

FIG. 1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG. 2 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 3 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS





FIG. 5 - TYPICAL THERMAL RESISTANCE VS LEAD LENGTH





6A05 THRU 6A10

Package Information

R-6

Dimensions in mm

