




BCW66F-G-H

NPN Transistor

Features

- BCW66 is subdivided into three groups F,G and H according to DC current gain

Marking



Rank	F	G	H
Marking	EF	EG	EH

Maximum Ratings($T_A=25^{\circ}\text{C}$, unless otherwise noted.)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	75	V
Collector-Emitter Voltage	V_{CEO}	45	V
Emitter-Base Voltage	V_{EBO}	5	V
Collector Current	I_{C}	800	mA
Collector Power Dissipation	P_{C}	200	mW
Junction Temperature	T_{J}	150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55~+150	$^{\circ}\text{C}$

Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal Resistance form Junction to Ambient	$R_{\theta\text{JA}}$	625	$^{\circ}\text{C}/\text{W}$

Electrical Characteristics($T_A=25^{\circ}\text{C}$, unless otherwise noted.)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(\text{BR})\text{CBO}}$	$I_{\text{C}}=10\mu\text{A}, I_{\text{E}}=0$	75			V
Collector-emitter breakdown voltage	$V_{(\text{BR})\text{CEO}}$	$I_{\text{C}}=10\text{mA}, I_{\text{B}}=0$	45			V
Emitter-base breakdown voltage	$V_{(\text{BR})\text{EBO}}$	$I_{\text{E}}=10\mu\text{A}, I_{\text{C}}=0$	5			V




BCW66F-G-H

Collector cut-off current	I_{CBO}	$V_{CB}=45V, I_E=0$			0.02	μA
Emitter cut-off current	I_{EBO}	$V_{EB}=4V, I_C=0$			0.02	μA
DC current gain	h_{FE1}	$V_{CE}=10V, I_C=0.1mA$	F	35		
			G	50		
			H	80		
	h_{FE2}	$V_{CE}=1V, I_C=10mA$	F	75		
			G	110		
			H	180		
	h_{FE3}	$V_{CE}=1V, I_C=100mA$	F	100		250
			G	160		400
			H	250		630
	h_{FE4}	$V_{CE}=2V, I_C=500mA$	F	35		
			G	60		
			H	100		
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=100mA, I_B=10mA$			0.3	V
		$I_C=500mA, I_B=50mA$			0.7	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C=500mA, I_B=50mA$			2	V
Transition frequency	f_T	$V_{CE}=10V, I_C=20mA,$ $f=100MHz$	100			MHz
Output Capacitance	C_{ob}	$V_{CB}=10V, I_E=0, f=1MHz$			12	pF
Input Capacitance	C_{ib}	$V_{EB}=0.5V, I_E=0, f=1MHz$			80	pF
Noise Figure	NF	$V_{CE}=5V, I_C=0.2mA, f=1KHz,$ $R_S=1K\Omega, BW=200Hz$			10	dB



BCW66F-G-H

Typical Characteristics






BCW66F-G-H

Package Information

SOT-23

Dimensions in mm



Unit	A	B	b _p	C	D	E	H _E	A ₁	L _p
mm	1.40 0.95	2.04 1.78	0.50 0.35	0.19 0.08	3.10 2.70	1.65 1.20	2.64 2.20	0.100 0.013	0.50 0.20



Shikues Disclaimer

1.Accuracy of Information and Right to Modify

The information provided in this document is for reference only. Shikues reserves the right to make changes to this document and to the specifications of the products described herein at any time, without prior notice, for the purpose of improving reliability, function, design, or for any other reason. It is the customer's responsibility to obtain and verify the latest product information and specifications before making any final design, procurement, or usage decisions.

2.No Warranty

Shikues makes no express or implied warranties, representations, or guarantees regarding the suitability of its products for any particular purpose.

Shikues assumes no liability for any assistance provided or for the design of customer products. All products are supplied "as is."

3.Intended Use and Limitation of Liability

The products described in this document are intended for use in general-purpose electronic devices. They are neither designed nor tested nor authorized for use in transportation equipment or applications requiring high reliability. Unless expressly authorized in writing by Shikues, these products must not be used as critical components in life-support systems or any applications where failure could directly pose a risk to human life (including, but not limited to, medical devices, transportation systems, aerospace equipment, nuclear facilities, and safety-critical systems).

Shikues assumes no responsibility or liability for any consequences arising from the use of its products in unauthorized or unintended applications.

Neither Shikues nor its representatives shall be held liable for any resulting damages.

4.Intellectual Property

This document does not grant any express or implied license—whether by estoppel, implication, or otherwise—to use any intellectual property rights of Shikues.