



# BZX84B Series



## Silicon Planar Zener Diodes

### Description

This series of Zener diodes is offered in the convenient, surface mount plastic SOT-23 package. These devices are designed to provide voltage regulation with minimum space requirement. They are well suited for applications such as cellular phones, hand held portables, and high density PC boards.

### Features

- Zener breakdown voltage range: 2.4V to 75V
- Package designed for optimal automated board assembly
- Small package size for high density applications



1.Anode 3.Cathode  
SOT-23 Plastic Package

### Absolute Maximum Ratings ( $T_A=25^{\circ}\text{C}$ unless otherwise noted)

| Parameter                                 | Symbol          | Value    | Unit                 |
|-------------------------------------------|-----------------|----------|----------------------|
| Power Dissipation                         | $P_D$           | 300      | mW                   |
| Junction and Storage Temperature Range    | $T_J, T_{STG}$  | -65~+150 | $^{\circ}\text{C}$   |
| Typical Thermal Resistance <sup>(1)</sup> | $R_{\theta JA}$ | 417      | $^{\circ}\text{C/W}$ |

Note:(1) Alumina = 0.4 x 0.3 x 0.024 in, 99.5% alumina

### Electrical Characteristics ( $T_A=25^{\circ}\text{C}$ unless otherwise noted, $V_F<0.9\text{V}$ @ $I_F=10\text{mA}$ )

| Type      | Marking | Zener Voltage Range <sup>(1)</sup> |        |        |             | Dynamic Impedance |                 |             | Reverse Leakage Current |          |
|-----------|---------|------------------------------------|--------|--------|-------------|-------------------|-----------------|-------------|-------------------------|----------|
|           |         | $V_{ZT}$                           |        |        | at $I_{ZT}$ | $Z_{ZT}$          | $Z_{ZK}$        | at $I_{ZK}$ | $I_R$                   | at $V_R$ |
|           |         | Min(V)                             | Nom(V) | Max(V) | (mA)        | Max( $\Omega$ )   | Max( $\Omega$ ) | (mA)        | Max(uA)                 | (V)      |
| BZX84B2V4 | CR      | 2.35                               | 2.4    | 2.45   | 5           | 100               | 600             | 1           | 50                      | 1        |
| BZX84B2V7 | CX      | 2.65                               | 2.7    | 2.75   | 5           | 100               | 600             | 1           | 20                      | 1        |
| BZX84B3V0 | CY      | 2.94                               | 3      | 3.06   | 5           | 95                | 600             | 1           | 10                      | 1        |
| BZX84B3V3 | CZ      | 3.23                               | 3.3    | 3.37   | 5           | 95                | 600             | 1           | 5                       | 1        |
| BZX84B3V6 | DA      | 3.53                               | 3.6    | 3.67   | 5           | 90                | 600             | 1           | 5                       | 1        |
| BZX84B3V9 | DB      | 3.82                               | 3.9    | 3.98   | 5           | 90                | 600             | 1           | 3                       | 1        |
| BZX84B4V3 | DC      | 4.21                               | 4.3    | 4.39   | 5           | 90                | 600             | 1           | 3                       | 1        |
| BZX84B4V7 | DD      | 4.61                               | 4.7    | 4.79   | 5           | 80                | 500             | 1           | 3                       | 2        |



## BZX84B Series






|           |    |      |     |      |   |     |     |     |      |      |
|-----------|----|------|-----|------|---|-----|-----|-----|------|------|
| BZX84B5V1 | DE | 5    | 5.1 | 5.2  | 5 | 60  | 480 | 1   | 2    | 2    |
| BZX84B5V6 | DF | 5.49 | 5.6 | 5.71 | 5 | 40  | 400 | 1   | 1    | 2    |
| BZX84B6V2 | DH | 6.08 | 6.2 | 6.32 | 5 | 10  | 150 | 1   | 3    | 4    |
| BZX84B6V8 | DJ | 6.66 | 6.8 | 6.94 | 5 | 15  | 80  | 1   | 2    | 4    |
| BZX84B7V5 | DK | 7.35 | 7.5 | 7.65 | 5 | 15  | 80  | 1   | 1    | 5    |
| BZX84B8V2 | DM | 8.04 | 8.2 | 8.36 | 5 | 15  | 80  | 1   | 0.7  | 5    |
| BZX84B9V1 | DN | 8.92 | 9.1 | 9.28 | 5 | 15  | 100 | 1   | 0.5  | 6    |
| BZX84B10  | DP | 9.8  | 10  | 10.2 | 5 | 20  | 150 | 1   | 0.2  | 7    |
| BZX84B11  | DR | 10.8 | 11  | 11.2 | 5 | 20  | 150 | 1   | 0.1  | 8    |
| BZX84B12  | DX | 11.8 | 12  | 12.2 | 5 | 25  | 150 | 1   | 0.1  | 8    |
| BZX84B13  | DY | 12.7 | 13  | 13.3 | 5 | 30  | 170 | 1   | 0.1  | 8    |
| BZX84B15  | DZ | 14.7 | 15  | 15.3 | 5 | 30  | 200 | 1   | 0.05 | 10.5 |
| BZX84B16  | EA | 15.7 | 16  | 16.3 | 5 | 40  | 200 | 1   | 0.05 | 11.2 |
| BZX84B18  | EB | 17.6 | 18  | 18.4 | 5 | 45  | 225 | 1   | 0.05 | 12.6 |
| BZX84B20  | EC | 19.6 | 20  | 20.4 | 5 | 55  | 225 | 1   | 0.05 | 14   |
| BZX84B22  | ED | 21.6 | 22  | 22.4 | 5 | 55  | 250 | 1   | 0.05 | 15.4 |
| BZX84B24  | EE | 23.5 | 24  | 24.5 | 5 | 70  | 250 | 1   | 0.05 | 16.8 |
| BZX84B27  | EF | 26.5 | 27  | 27.5 | 2 | 80  | 300 | 0.5 | 0.05 | 18.9 |
| BZX84B30  | EH | 29.4 | 30  | 30.6 | 2 | 80  | 300 | 0.5 | 0.05 | 21   |
| BZX84B33  | EJ | 32.3 | 33  | 33.7 | 2 | 80  | 325 | 0.5 | 0.05 | 23.1 |
| BZX84B36  | EK | 35.3 | 36  | 36.7 | 2 | 90  | 350 | 0.5 | 0.05 | 25.2 |
| BZX84B39  | EM | 38.2 | 39  | 39.8 | 2 | 130 | 350 | 0.5 | 0.05 | 27.3 |
| BZX84B43  | EN | 42.1 | 43  | 43.9 | 2 | 150 | 375 | 0.5 | 0.05 | 30.1 |
| BZX84B47  | EP | 46.1 | 47  | 47.9 | 2 | 170 | 375 | 0.5 | 0.05 | 32.9 |
| BZX84B51  | ER | 50   | 51  | 52   | 2 | 180 | 400 | 0.5 | 0.05 | 35.7 |
| BZX84B56  | EX | 54.9 | 56  | 57.1 | 2 | 200 | 425 | 0.5 | 0.05 | 39.2 |
| BZX84B62  | EY | 60.8 | 62  | 63.2 | 2 | 215 | 450 | 0.5 | 0.05 | 43.4 |
| BZX84B68  | EZ | 66.6 | 68  | 69.4 | 2 | 240 | 475 | 0.5 | 0.05 | 47.6 |
| BZX84B75  | FA | 73.5 | 75  | 76.5 | 2 | 255 | 500 | 0.5 | 0.05 | 52.5 |


Note:(1)Tested with pulses  $t_p = 20\text{ms}$ .



# BZX84B Series

## Typical Characteristics






# BZX84B Series

## Package Information

### SOT-23

### Dimensions in mm



| UNIT | A            | B            | bp           | C            | D            | E            | HE           | A <sub>1</sub> | L <sub>p</sub> |
|------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|----------------|----------------|
| mm   | 1.40<br>0.95 | 2.04<br>1.78 | 0.50<br>0.35 | 0.19<br>0.08 | 3.10<br>2.70 | 1.65<br>1.20 | 3.00<br>2.20 | 0.100<br>0.013 | 0.50<br>0.20   |



## Shikues Disclaimer

### 1.Accuracy of Information and Right to Modify

The information provided in this document is for reference only. Shikues reserves the right to make changes to this document and to the specifications of the products described herein at any time, without prior notice, for the purpose of improving reliability, function, design, or for any other reason. It is the customer's responsibility to obtain and verify the latest product information and specifications before making any final design, procurement, or usage decisions.

### 2.No Warranty

Shikues makes no express or implied warranties, representations, or guarantees regarding the suitability of its products for any particular purpose.

Shikues assumes no liability for any assistance provided or for the design of customer products. All products are supplied "as is."

### 3.Intended Use and Limitation of Liability

The products described in this document are intended for use in general-purpose electronic devices. They are neither designed nor tested nor authorized for use in transportation equipment or applications requiring high reliability. Unless expressly authorized in writing by Shikues, these products must not be used as critical components in life-support systems or any applications where failure could directly pose a risk to human life (including, but not limited to, medical devices, transportation systems, aerospace equipment, nuclear facilities, and safety-critical systems).

Shikues assumes no responsibility or liability for any consequences arising from the use of its products in unauthorized or unintended applications.

Neither Shikues nor its representatives shall be held liable for any resulting damages.

### 4.Intellectual Property

This document does not grant any express or implied license—whether by estoppel, implication, or otherwise—to use any intellectual property rights of Shikues.