



ESD05D6BN

DESCRIPTION

ESD05D6BN is a low-capacitance Transient Voltage Suppressor (TVS) designed to provide electrostatic discharge (ESD) protection for data, control or power lines. With maximum capacitance of 18pF, ESD05D6BN is designed to protect parasitic-sensitive systems against over-voltage and over-current transient events. It complies with IEC 61000-4-2 (ESD), Level 4 ($\pm 15\text{kV}$ air, $\pm 8\text{kV}$ contact discharge), IEC 61000-4-4 (electrical fast transient - EFT) (40A, 5/50 ns), very fast charged device model (CDM) ESD and cable discharge event (CDE) etc.

ESD05D6BN uses ultra-small DFN0603 package. Each ESD05D6BN device can protect one data line. It offers system designers flexibility to protect single data line where space is a premium concern.

ORDERING INFORMATION

- ☐ Device: ESD05D6BN
- ☐ Package: DFN0603
- ☐ Marking: 5BN
- ☐ Material: Halogen free
- ☐ Packing: Tape & Reel
- ☐ Quantity per reel: 15,000pcs

PIN CONFIGURATION



FEATURES

- ☐ Transient protection for high-speed data lines
IEC 61000-4-2 (ESD) $\pm 30\text{kV}$ (Contact)
 $\pm 30\text{kV}$ (Air)
IEC 61000-4-4 (EFT) 40A (5/50 ns)
- ☐ Peak power dissipation: 72W (8/20 μs)
- ☐ Working voltages :5V
- ☐ Ultra-small package (0.6mm $\times$ 0.3mm $\times$ 0.3mm)
- ☐ Protects one I/O line
- ☐ Low clamping voltage
- ☐ Low leakage current


MACHANICAL DATA


- ☐ DFN0603 package
- ☐ Flammability Rating: UL 94V-0
- ☐ High temperature soldering guaranteed:
260 $^{\circ}\text{C}$ /10s
- ☐ Packaging: Tape and Reel
- ☐ Reel size: 7 inch

APPLICATIONS

- ☐ Personal digital assistants (PDA's)
- ☐ Notebooks, Desktops, and Servers
- ☐ Cell phone Handsets and Accessories
- ☐ Portable Electronics
- ☐ IOT Terminal Equipment/Device
- ☐ Smart Wearable Device

CIRCUIT DIAGRAM





ESD05D6BN

ABSOLUTE MAXIMUM RATING

Symbol	Parameter	Value	Units
V_{ESD}	ESD per IEC 61000-4-2 (Contact)	± 30	kV
	ESD per IEC 61000-4-2 (Air)	± 30	
P_{PP}	Peak Pulse Power (8/20 μ s)	72	W
T_{OPT}	Operating Temperature	-55~125	$^{\circ}$ C
T_{STG}	Storage Temperature	-55~150	$^{\circ}$ C

ELECTRICAL CHARACTERISTICS (Tamb=25 $^{\circ}$ C)

Symbol	Parameter	Test Condition	Min	Typ	Max	Units
V_{RWM}	Reverse Working Voltage				5.0	V
V_{BR}	Reverse Breakdown Voltage	$I_T = 1mA$	5.6			V
I_R	Reverse Leakage Current	$V_{RWM} = 5V$			1.0	μA
V_C	Clamping Voltage	$I_{PP} = 1A, t_p = 8/20\mu s$		6.5	8.0	V
		$I_{PP} = 6A, t_p = 8/20\mu s$		10.0	12.0	V
$V_{CTL P}$	TLP Clamping Voltage	$I_{PP} = 16A$ IEC61000-4-2 Level 4 equivalent ($\pm 8kV$ Contact, $\pm 15kV$ Air)		9.5		V
C_J	Junction Capacitance	$V_R = 0V, f = 1MHz$		14.0	18.0	pF

ELECTRICAL CHARACTERISTICS CURVE

Fig 1 8/20 μ s Waveform per IEC61000-4-5




Fig 2 Contact Discharge Current Waveform per IEC 61000-4-2)




Fig 3 Power Derating Curve




Fig 4 Voltage vs Capacitance




Fig 5 Transmission Line Pulsing (TLP) Measurement






Fig 6 Clamping Voltage vs Peak Pulse Current



DFN0603 PACKAGE OUTLINE DIMENSIONS



Dimensions in Millimeter			
Symbol	Min.	Typ.	Max.
A	0.58	0.60	0.65
B	0.28	0.30	0.35
C	0.28	0.30	0.34
D	0.20	0.24	0.26
E	0.13	0.16	0.19
F		0.36	