



ESD3B5CM

Bidirectional TVS/ESD Diode Array


Description

The ESD3B5CM is designed to protect voltage sensitive components from ESD and transient voltage events. Excellent clamping capability, low leakage, and fast response time, make these parts ideal for ESD protection on designs where board space is at a premium. Because of its small size, it is suited for use in cellular phones, portable devices, digital cameras, power supplies and many other portable applications where board space comes at a premium. Also because of its low capacitance, it is suited for use in high frequency designs such as high speed line applications. This device has been specifically designed to protect sensitive components which are connected to data and transmission lines from overvoltage caused by ESD (electrostatic discharge), and EFT (electrical fast transients).

Ordering Information

- Device:ESD3B5CM
- Package:SOD-323
- Marking:2B
- Material:Halogen free and RoHS compliant
- Packing:Tape & Reel
- Quantity per reel:3,000pcs

Pin Configuration



Features

- ESD per IEC 61000-4-2 $\pm 30\text{kV}$ (Contact)
- ESD per IEC 61000-4-2 $\pm 30\text{kV}$ (Air)
- IEC61000-4-4(EFT) 40A(5/50ns)
- Peak power dissipation: 500W(8/20 μs)
- Protects one V_{CC} or data line
- Low clamping voltage
- Working voltage: 5V
- Low leakage current
- Low capacitance

Mechanical Data

- SOD-323 package
- Flammability Rating: UL 94V-0
- High temperature soldering guaranteed: 260°C/10s
- Packaging: Tape and Reel
- Reel size: 7 inch

Applications

- Cell Phone Handsets and Accessories
- Microprocessor based equipment
- Personal Digital Assistants(PDA's)
- Notebooks, Desktops, and Servers
- Portable Instrumentation
- Networking and Telecom
- Serial and Parallel Ports
- Peripherals

Package Outline





ESD3B5CM

Absolute Maximum Rating

Parameter	Symbol	Value	Unit
ESD per IEC 61000-4-2(Air)	V_{ESD}	± 30	kV
ESD per IEC 61000-4-2(Contact)		± 30	kV
Peak Pulse Power(8/20 μ s)	P_{PP}	500	W
Operating Temperature	T_{OPT}	-55~+150	°C
Storage Temperature	T_{STG}	-55~+150	°C

Electrical Characteristics ($T_A=25^{\circ}\text{C}$)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Reverse Working Voltage	V_{RWM}				5.0	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1\text{mA}$	5.8		7.8	V
Reverse Leakage Current	I_R	$V_{RWM}=5\text{V}$			1.0	μA
Clamping Voltage	V_C	$I_{PP}=1\text{A}, t_p=8/20\mu\text{s}$			9.8	V
		$I_{PP}=25\text{A}, t_p=8/20\mu\text{s}$		15	20	V
Junction Capacitance	C_J	$V_R=0\text{V}, f=1\text{MHz}$			50	pF



Typical Characteristics

Fig1 8/20 μ s Pulse Waveform




Fig2 Contact Discharge Current Waveform (IEC 61000-4-2)




Fig 3 Voltage vs Capacitance





Fig 4 Peak Pulse Current vs Clamping Voltage






ESD3B5CM


Package Information

SOD-323

Dimensions in mm



Symbol	Dimensions In Millimeters	
	Min	Max
A		1.00
A1	0.000	0.100
A2	0.800	0.900
b	0.250	0.350
c	0.080	0.150
D	1.200	1.400
E	1.600	1.800
E1	2.500	2.700
e	1.800	2.040
L	0.475 REF	
L1	0.250	0.400
θ	0°	8°



Shikues Disclaimer

1.Accuracy of Information and Right to Modify

The information provided in this document is for reference only. Shikues reserves the right to make changes to this document and to the specifications of the products described herein at any time, without prior notice, for the purpose of improving reliability, function, design, or for any other reason. It is the customer's responsibility to obtain and verify the latest product information and specifications before making any final design, procurement, or usage decisions.

2.No Warranty

Shikues makes no express or implied warranties, representations, or guarantees regarding the suitability of its products for any particular purpose.

Shikues assumes no liability for any assistance provided or for the design of customer products. All products are supplied "as is."

3.Intended Use and Limitation of Liability

The products described in this document are intended for use in general-purpose electronic devices. They are neither designed nor tested nor authorized for use in transportation equipment or applications requiring high reliability. Unless expressly authorized in writing by Shikues, these products must not be used as critical components in life-support systems or any applications where failure could directly pose a risk to human life (including, but not limited to, medical devices, transportation systems, aerospace equipment, nuclear facilities, and safety-critical systems).

Shikues assumes no responsibility or liability for any consequences arising from the use of its products in unauthorized or unintended applications.

Neither Shikues nor its representatives shall be held liable for any resulting damages.

4.Intellectual Property

This document does not grant any express or implied license—whether by estoppel, implication, or otherwise—to use any intellectual property rights of Shikues.