



GBLCxxCI Series

Bidirectional TVS Diode Array

Description


The GBLCxxCI Series is designed for applications requiring transient overvoltage protection capability. They are intended for use in voltage and ESD sensitive equipment such as computers, printers, business machines, communication systems, medical equipment and other applications. These devices are ideal for situations where board space is at a premium.

This series has been specifically designed to protect sensitive components which are connected to power data and transmission lines from overvoltage caused by ESD (electrostatic discharge), CDE (Cable Discharge Events), and EFT (electrical fast transients).

Ordering Information

- Device:GBLCxxCI
- Package:SOD-323
- Material:Halogen free and RoHS compliant
- Packing:Tape & Reel
- Quantity per reel:3,000pcs

Pin Configuration



Features

- IEC 61000-4-2(ESD) $\pm 30\text{kV}$ (Contact)
 $\pm 30\text{kV}$ (Air)
- IEC61000-4-4(EFT) 40A(5/50ns)
- 450W peak pulse power per ($t_p=8/20\mu\text{s}$)
- Protects two bidirectional lines
- Low clamping voltage
- Working voltage: 3.3V to 36V
- Low leakage current

Mechanical Data

- SOD-323 package
- Flammability Rating: UL 94V-0
- High temperature soldering guaranteed:
260°C/10s
- Packaging: Tape and Reel
- Reel size: 7 inch

Applications

- Cell Phone Handsets and Accessories
- Microprocessor based equipment
- Personal Digital Assistants(PDA's)
- Notebooks, Desktops, and Servers
- Portable Instrumentation
- Networking and Telecom
- Serial and Parallel Ports
- Peripherals

Package Outline






GBLCxxCI Series

Absolute Maximum Rating

Parameter	Symbol	Value	Unit
ESD per IEC 61000-4-2(Air)	V_{ESD}	± 30	kV
ESD per IEC 61000-4-2(Contact)		± 30	kV
Peak Pulse Power(8/20 μ s)	P_{PP}	450	W
Operating Temperature	T_{OPT}	-55~+150	°C
Storage Temperature	T_{STG}	-55~+150	°C
Lead Soldering Temperature(10 sec.)	T_L	260	°C

Electrical Characteristics ($T_A=25^{\circ}\text{C}$)

Part Number	Device Marking	V_{RWM} (V) (max.)	V_{BR} (V) (min.)	I_T (mA)	$V_C@1A$ (V) (max.)	V_C (V) (max.) @A		I_R (μ A) (max.)	C_J (pF) (typ.)
GBLC03CI	CC	3.3	4.0	1	7.0	18.0	23	2	0.8
GBLC05CI	AC	5.0	6.0	1	9.8	19.0	22	1	0.8
GBLC08CI	BC	8.0	8.5	1	13.4	24.0	20	1	0.8
GBLC12CI	DC	12.0	13.3	1	19.0	29.0	17	1	0.8
GBLC15CI	EC	15.0	16.7	1	24.0	34.0	13	1	0.8
GBLC18CI	FC	18.0	20.0	1	29.0	50.0	10	1	0.8
GBLC20CI	GC	20.0	22.3	1	35.0	53.0	9	1	0.8
GBLC24CI	HC	24.0	26.7	1	43.0	55.0	9	1	0.8
GBLC36CI	IC	36.0	40.0	1	60.0	75.0	6	1	0.8



GBLCxxCI Series

Typical Characteristics

Fig1. 8/20 μ s Pulse Waveform




Fig2. Contact Discharge Current Waveform (IEC 61000-4-2)




Fig3 Clamping Voltage vs Peak Pulse Current




Fig4 Clamping Voltage vs Peak Pulse Current





Fig5 Capacitance vs Reverse Voltage






GBLCxxCI Series


Package Information

SOD-323

Dimensions in mm



Symbol	Dimensions In Millimeters	
	Min	Max
A		1.00
A1	0.000	0.100
A2	0.800	0.900
b	0.250	0.350
c	0.080	0.150
D	1.200	1.400
E	1.600	1.800
E1	2.500	2.700
e	1.800	2.040
L	0.475 REF	
L1	0.250	0.400
θ	0°	8°



Shikues Disclaimer

1.Accuracy of Information and Right to Modify

The information provided in this document is for reference only. Shikues reserves the right to make changes to this document and to the specifications of the products described herein at any time, without prior notice, for the purpose of improving reliability, function, design, or for any other reason. It is the customer's responsibility to obtain and verify the latest product information and specifications before making any final design, procurement, or usage decisions.

2.No Warranty

Shikues makes no express or implied warranties, representations, or guarantees regarding the suitability of its products for any particular purpose.

Shikues assumes no liability for any assistance provided or for the design of customer products. All products are supplied "as is."

3.Intended Use and Limitation of Liability

The products described in this document are intended for use in general-purpose electronic devices. They are neither designed nor tested nor authorized for use in transportation equipment or applications requiring high reliability. Unless expressly authorized in writing by Shikues, these products must not be used as critical components in life-support systems or any applications where failure could directly pose a risk to human life (including, but not limited to, medical devices, transportation systems, aerospace equipment, nuclear facilities, and safety-critical systems).

Shikues assumes no responsibility or liability for any consequences arising from the use of its products in unauthorized or unintended applications.

Neither Shikues nor its representatives shall be held liable for any resulting damages.

4.Intellectual Property

This document does not grant any express or implied license—whether by estoppel, implication, or otherwise—to use any intellectual property rights of Shikues.