



KBU15005 THRU KBU1510

Glass Passivated Bridge Rectifiers

Reverse Voltage - 50 to 1000V Forward Current - 15A

Features

- Glass passivated chip
- Low forward voltage drop
- Ideal for printed circuit board
- High surge current capability
- Meet UL flammability classification 94V-0

Applications

- General purpose use in AC/DC bridge full wave rectification, for SMPS, lighting ballast, adapter, etc.


Maximum Ratings and Electrical Characteristics

(Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate by 20 %)

Parameter		Symbol	KBU 15005	KBU 1501	KBU 1502	KBU 1504	KBU 1506	KBU 1508	KBU 1510	Unit
Maximum Repetitive Peak Reverse Voltage		V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage		V _{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage		V _{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current @T _C =100°C	with heatsink ⁽¹⁾	I _(AV)	15.0						A	
	without heatsink		3.2							
Peak Forward Surge Current,8.3ms Single Half Sine-wave, Superimposed on Rated Load (JEDEC method)		I _{FSM}	250						A	
I ² t Rating for Fusing(t<8.3mS)		I ² t	259.4						A ² S	
Peak Forward Voltage per Diode at 7.5A DC		V _F	1.0						V	
Maximum DC Reverse Current at Rated DC Blocking Voltage per Diode	T _J =25°C	I _R	10						μA	
	T _J =125°C		500							
Operating Junction Temperature Range		T _J	-55~+150						°C	
Storage Temperature Range		T _{STG}	-55~+150						°C	

Notes: (1). Measured at 1.0MHz and applied reverse voltage of 4.0V DC

KBU



RoHS
COMPLIANT



KBU15005 THRU KBU1510

Typical Characteristics

Fig. 1 - Forward Current Derating Curve




Fig. 2 - Maximum Non-Repetitive Surge Current




Fig. 3 - Typical Reverse Characteristics






Fig. 4 - Typical Forward Characteristics






KBU15005 THRU KBU1510

Package Information

KBU

Dimensions in Inches (Millimeters)





KBU15005 THRU KBU1510

Shikues Disclaimer

1.Accuracy of Information and Right to Modify

The information provided in this document is for reference only. Shikues reserves the right to make changes to this document and to the specifications of the products described herein at any time, without prior notice, for the purpose of improving reliability, function, design, or for any other reason. It is the customer's responsibility to obtain and verify the latest product information and specifications before making any final design, procurement, or usage decisions.

2.No Warranty

Shikues makes no express or implied warranties, representations, or guarantees regarding the suitability of its products for any particular purpose.

Shikues assumes no liability for any assistance provided or for the design of customer products. All products are supplied "as is."

3.Intended Use and Limitation of Liability

The products described in this document are intended for use in general-purpose electronic devices. They are neither designed nor tested nor authorized for use in transportation equipment or applications requiring high reliability. Unless expressly authorized in writing by Shikues, these products must not be used as critical components in life-support systems or any applications where failure could directly pose a risk to human life (including, but not limited to, medical devices, transportation systems, aerospace equipment, nuclear facilities, and safety-critical systems).

Shikues assumes no responsibility or liability for any consequences arising from the use of its products in unauthorized or unintended applications.

Neither Shikues nor its representatives shall be held liable for any resulting damages.

4.Intellectual Property

This document does not grant any express or implied license—whether by estoppel, implication, or otherwise—to use any intellectual property rights of Shikues.