



# MMSZ4678 THRU MMSZ4717

## Silicon Planar Power Zener Diodes

### Features

- Zener Voltage : 1.8V~43V
- Wide Zener Reverse Voltage Range
- Small Package Size for High Density Applications

### Maximum Ratings (T<sub>A</sub>=25°C unless otherwise Specified)

| Parameter                               | Symbol                           | Value    | Unit |
|-----------------------------------------|----------------------------------|----------|------|
| Forward Voltage@I <sub>F</sub> =10mA    | V <sub>F</sub>                   | 0.9      | V    |
| Power Dissipation                       | P <sub>D</sub>                   | 350      | mW   |
| Operating and Storage Temperature Range | T <sub>J</sub> ,T <sub>STG</sub> | -55~+150 | °C   |
| Operating and Storage Temperature Range | R <sub>θJA</sub>                 | 357      | °C/W |


Notes:Device mounted on ceramic PCB;5.0mm x 7.0mm with pad areas 35mm<sup>2</sup>

### Electrical Characteristics (T<sub>A</sub>=25°C unless otherwise Specified)

| Type     | Marking | Zenner Voltage Range <sup>(1)</sup>   |     |       |                 | Leakage Current                     |                |
|----------|---------|---------------------------------------|-----|-------|-----------------|-------------------------------------|----------------|
|          |         | V <sub>ZT</sub> (at I <sub>ZT</sub> ) |     |       | I <sub>ZT</sub> | I <sub>R</sub> (at V <sub>R</sub> ) | V <sub>R</sub> |
|          |         | Min                                   | Nom | Max   | μA              | μA                                  | V              |
| MMSZ4678 | CC      | 1.71                                  | 1.8 | 1.89  | 50              | 7.5                                 | 1              |
| MMSZ4679 | CD      | 1.90                                  | 2.0 | 2.10  | 50              | 5                                   | 1              |
| MMSZ4680 | CE      | 2.09                                  | 2.2 | 2.31  | 50              | 4                                   | 1              |
| MMSZ4681 | CF      | 2.28                                  | 2.4 | 2.52  | 50              | 2                                   | 1              |
| MMSZ4682 | CH      | 2.565                                 | 2.7 | 2.835 | 50              | 1                                   | 1              |
| MMSZ4683 | CJ      | 2.85                                  | 3.0 | 3.15  | 50              | 0.8                                 | 1              |
| MMSZ4684 | CK      | 3.13                                  | 3.3 | 3.47  | 50              | 7.5                                 | 1.5            |
| MMSZ4685 | CM      | 3.42                                  | 3.6 | 3.78  | 50              | 7.5                                 | 2              |
| MMSZ4686 | CN      | 3.70                                  | 3.9 | 4.10  | 50              | 5                                   | 2              |
| MMSZ4687 | CP      | 4.09                                  | 4.3 | 4.52  | 50              | 4                                   | 2              |
| MMSZ4688 | CT      | 4.47                                  | 4.7 | 4.94  | 50              | 10                                  | 3              |

### PINNING

| PIN | DESCRIPTION |
|-----|-------------|
| 1   | Cathode     |
| 2   | Anode       |





## MMSZ4678 THRU MMSZ4717

|          |    |       |     |       |    |      |      |
|----------|----|-------|-----|-------|----|------|------|
| MMSZ4689 | CU | 4.85  | 5.1 | 5.36  | 50 | 10   | 3    |
| MMSZ4690 | CV | 5.32  | 5.6 | 5.88  | 50 | 10   | 4    |
| MMSZ4691 | CA | 5.89  | 6.2 | 6.51  | 50 | 10   | 5    |
| MMSZ4692 | CX | 6.46  | 6.8 | 7.14  | 50 | 10   | 5.1  |
| MMSZ4693 | CY | 7.13  | 7.5 | 7.88  | 50 | 10   | 5.7  |
| MMSZ4694 | CZ | 7.79  | 8.2 | 8.61  | 50 | 1    | 6.2  |
| MMSZ4695 | DC | 8.27  | 8.7 | 9.14  | 50 | 1    | 6.6  |
| MMSZ4696 | DD | 8.65  | 9.1 | 9.56  | 50 | 1    | 6.9  |
| MMSZ4697 | DE | 9.50  | 10  | 10.50 | 50 | 1    | 7.6  |
| MMSZ4698 | DF | 10.45 | 11  | 11.55 | 50 | 0.05 | 8.4  |
| MMSZ4699 | DH | 11.40 | 12  | 12.60 | 50 | 0.05 | 9.1  |
| MMSZ4700 | DJ | 12.35 | 13  | 13.65 | 50 | 0.05 | 9.8  |
| MMSZ4701 | DM | 13.30 | 14  | 14.70 | 50 | 0.05 | 10.6 |
| MMSZ4702 | DK | 14.25 | 15  | 15.75 | 50 | 0.05 | 11.4 |
| MMSZ4703 | DN | 15.20 | 16  | 16.80 | 50 | 0.05 | 12.1 |
| MMSZ4704 | DP | 16.15 | 17  | 17.85 | 50 | 0.05 | 12.9 |
| MMSZ4705 | DT | 17.10 | 18  | 18.90 | 50 | 0.05 | 13.6 |
| MMSZ4706 | DU | 18.05 | 19  | 19.95 | 50 | 0.05 | 14.4 |
| MMSZ4707 | DV | 19.00 | 20  | 21.00 | 50 | 0.01 | 15.2 |
| MMSZ4708 | DA | 20.90 | 22  | 23.10 | 50 | 0.01 | 16.7 |
| MMSZ4709 | DX | 22.80 | 24  | 25.20 | 50 | 0.01 | 18.2 |
| MMSZ4710 | DY | 23.75 | 25  | 26.25 | 50 | 0.01 | 19.0 |
| MMSZ4711 | EA | 25.65 | 27  | 28.35 | 50 | 0.01 | 20.4 |
| MMSZ4712 | EC | 26.60 | 28  | 29.40 | 50 | 0.01 | 21.2 |
| MMSZ4713 | ED | 28.50 | 30  | 31.50 | 50 | 0.01 | 22.8 |
| MMSZ4714 | EE | 31.35 | 33  | 34.65 | 50 | 0.01 | 25.0 |
| MMSZ4715 | EF | 34.20 | 36  | 37.80 | 50 | 0.01 | 27.3 |
| MMSZ4716 | EH | 37.05 | 39  | 40.95 | 50 | 0.01 | 29.6 |
| MMSZ4717 | EJ | 40.85 | 43  | 45.15 | 50 | 0.01 | 32.6 |

Note:

(1) Nominal Zener voltage is measured with the device junction in thermal equilibrium at  $T_L = 30^\circ\text{C} \pm 1^\circ\text{C}$



# MMSZ4678 THRU MMSZ4717

## Typical Characteristics




**Figure 1. Temperature Coefficients**  
(Temperature Range -55°C to +150°C)




**Figure 2. Temperature Coefficients**  
(Temperature Range -55°C to +150°C)




**Figure 3. Steady State Power Derating**




**Figure 4. Maximum Nonrepetitive Surge Power**




**Figure 5. Effect of Zener Voltage on**  
Zener Impedance




**Figure 6. Typical Forward Voltage**



# MMSZ4678 THRU MMSZ4717




Figure 7. Typical Capacitance




Figure 8. Typical Leakage Current




Figure 9. Zener Voltage versus Zener Current  
( $V_Z$  Up to 12 V)





Figure 10. Zener Voltage versus Zener Current  
(12 to 43 V)




# MMSZ4678 THRU MMSZ4717


## Package Information

### SOD-123

### Dimensions in mm



| UNIT | A            | bp           | C              | D            | E            | HE           | A1           | LP           |
|------|--------------|--------------|----------------|--------------|--------------|--------------|--------------|--------------|
| mm   | 1.20<br>0.90 | 0.60<br>0.50 | 0.135<br>0.100 | 2.75<br>2.55 | 1.65<br>1.55 | 3.85<br>3.55 | 0.10<br>0.01 | 0.50<br>0.20 |



# MMSZ4678 THRU MMSZ4717

---

## Shikues Disclaimer

### 1.Accuracy of Information and Right to Modify

The information provided in this document is for reference only. Shikues reserves the right to make changes to this document and to the specifications of the products described herein at any time, without prior notice, for the purpose of improving reliability, function, design, or for any other reason. It is the customer's responsibility to obtain and verify the latest product information and specifications before making any final design, procurement, or usage decisions.

### 2.No Warranty

Shikues makes no express or implied warranties, representations, or guarantees regarding the suitability of its products for any particular purpose.

Shikues assumes no liability for any assistance provided or for the design of customer products. All products are supplied "as is."

### 3.Intended Use and Limitation of Liability

The products described in this document are intended for use in general-purpose electronic devices. They are neither designed nor tested nor authorized for use in transportation equipment or applications requiring high reliability. Unless expressly authorized in writing by Shikues, these products must not be used as critical components in life-support systems or any applications where failure could directly pose a risk to human life (including, but not limited to, medical devices, transportation systems, aerospace equipment, nuclear facilities, and safety-critical systems).

Shikues assumes no responsibility or liability for any consequences arising from the use of its products in unauthorized or unintended applications.

Neither Shikues nor its representatives shall be held liable for any resulting damages.

### 4.Intellectual Property

This document does not grant any express or implied license—whether by estoppel, implication, or otherwise—to use any intellectual property rights of Shikues.