



PESD5V0S1BL

Transient Voltage Suppressors for ESD Protection

General Description

The is designed to protect voltage Sensitive components from ESD and transient voltage events. Excellent clamping capability, low leakage, and fast response time, make these parts ideal for ESD protection on designs where board space is at a premium. Because of its small size, it is suited for use in cellular phones, MP3 players, digital cameras and many other portable applications where board space is at a premium.

Applications



- Cellular phones
- Portable devices
- Digital cameras
- Power supplies

Features

- Small Body Outline Dimensions
- Low Body Height
- Peak Power up to 150 Watts @ 8 x 20 μ s Pulse
- Low Leakage current
- Response Time is Typically < 1 ns
- ESD Rating of Class 3 (> 16 kV) per Human Body Model


Absolute Ratings ($T_{amb}=25^{\circ}\text{C}$)

Symbol	Parameter	Value	Units
P _{pp}	Peak Pulse Power (t _p = 8/20 μ s)	150	W
T _L	Maximum lead temperature for soldering during 10s	260	°C
T _{stg}	Storage Temperature Range	-55 to +155	°C
T _{op}	Operating Temperature Range	-40 to +125	°C
T _j	Maximum junction temperature	150	°C
	IEC61000-4-2 (ESD) air discharge contact discharge	± 15 ± 8	KV
	IEC61000-4-4 (EFT)	40	A
	ESD Voltage Per Human Body Model	16	KV



Electrical Parameter

Symbol	Parameter
I_{PP}	Reverse Peak Pulse
V_C	Capacitance @ I_{PP}
V_{RWM}	Reverse Voltage
I_R	Reverse Leakage Current
I_T	Test Current
V_{BR}	Breakdown Voltage @ I_T



Electrical Characteristics Ratings at 25°C ambient temperature unless otherwise specified. $V_F = 0.9V$ at $I_F = 10mA$

Device	V_{RWM} (V)	$I_{R1}(uA)$ @ V_{RWM}	$I_{R2}(uA)$ @ $V_R=3.5V$	V_{BR} (V)@ I_T (Note 1)	I_T mA	V_C (V) @ $I_{PP}=5A^*$	V_C (V) @ Max I_{PP}^*	I_{PP} (A)*	P_{PK} (W)*	C (pF)
	Max	Max	Max	Min		Typ	Max	Max	Max	Typ
PESD5V0S1BL	5.0	0.5	0.3	5.6	1.0	11.6	18.6	9.4	174	15

*Surge current waveform per Figure 1.

1. V_{BR} is measured with a pulse test current I_T at an ambient temperature of 25°C.




Fig1. Pulse Waveform




Fig2. Power Derating Curve



PESD5V0S1BL

SOD882 DIMENSION OUTLINE

Unit:mm

