



SD103AW THRU SD103CW

Schottky Barrier Rectifiers

Features


- Low forward voltage drop
- Guard ring ring construction for transient protection
- Negligible reverse recovery time
- Low capacitance

Maximum Ratings And Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode



Top View
Marking Code: S4~S6
Simplified outline SOD-123 and symbol

Parameter		Symbol	SD103AW	SD103BW	SD103CW	Units
Peak Repetitive Reverse Voltage		V _{RRM}	40	30	20	V
RMS Reverse Voltage		V _{RMS}	28	21	14	V
Working Peak Reverse Voltage		V _{DC}	40	30	20	V
Peak Forward Surge Current@8.3 ms		I _{FSM}	2			A
Maximum Instantaneous Forward Voltage	I _F =20mA	V _F	0.37			V
	I _F =200mA		0.60			
Power Dissipation		P _D	400			mW
Reverse Current	SD103AW,V _R =30V		I _R	5		uA
	SD103BW,V _R =20V				5	
	SD103CW,V _R =10V					
Thermal Resistance Junction to Ambient		R _{θJA}	300			°C/W
Reverse Voltage I _R =100uA	SD103AW		V _{BR}	40		V
	SD103BW			30		
	SD103CW			20		
Reverse Recovery time I _F =I _R =200mA,I _{tr} =0.1xI _R ,R _L =100Ω		t _{rr}	10			ns
Forward Continuous Current		I _F	350			mA
Total Capacitance V _R =0V,f=1MHz		C _{tot}	28			pF
Junction Temperature		T _J	125			°C
Storage Temperature		T _{STG}	-55~+150			°C



SD103AW THRU SD103CW

Typical Characteristic

Fig.1 Power Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Forward Characteristics




Fig.4 Typical Transient Thermal Impedance





Fig.5 Typical Junction Capacitance






SD103AW THRU SD103CW

Package Information


SOD-123

Dimensions in mm



Unit		A	C	D	E	E ₁	L ₁	b	A ₁	∠
mm	max	1.3	0.22	1.8	2.8	3.9	0.45	0.7	0.2	9°
	min	0.9	0.09	1.5	2.5	3.6	0.25	0.5	-	
mil	max	51	8.7	71	110	154	18	28	8	
	min	35	3.5	59	98	142	10	20	-	

The recommended mounting pad size





SD103AW THRU SD103CW

Shikues Disclaimer

1.Accuracy of Information and Right to Modify

The information provided in this document is for reference only. Shikues reserves the right to make changes to this document and to the specifications of the products described herein at any time, without prior notice, for the purpose of improving reliability, function, design, or for any other reason. It is the customer's responsibility to obtain and verify the latest product information and specifications before making any final design, procurement, or usage decisions.

2.No Warranty

Shikues makes no express or implied warranties, representations, or guarantees regarding the suitability of its products for any particular purpose.

Shikues assumes no liability for any assistance provided or for the design of customer products. All products are supplied "as is."

3.Intended Use and Limitation of Liability

The products described in this document are intended for use in general-purpose electronic devices. They are neither designed nor tested nor authorized for use in transportation equipment or applications requiring high reliability. Unless expressly authorized in writing by Shikues, these products must not be used as critical components in life-support systems or any applications where failure could directly pose a risk to human life (including, but not limited to, medical devices, transportation systems, aerospace equipment, nuclear facilities, and safety-critical systems).

Shikues assumes no responsibility or liability for any consequences arising from the use of its products in unauthorized or unintended applications.

Neither Shikues nor its representatives shall be held liable for any resulting damages.

4.Intellectual Property

This document does not grant any express or implied license—whether by estoppel, implication, or otherwise—to use any intellectual property rights of Shikues.