Wire Wound SMD Power Inductors

FEATURES

- Magnetic shield structure
- High current, low DC resistance
- Composite structure, ultra-low noise
- Good weldability and high heat resistance

APPLICATIONS

- PDA/Laptop, Desktop/Server, etc
- High current POL converter
- High current power supply, battery powered equipment
- DC-DC conversion of distributed power systems
- DC-DC conversion for field programmable gate arrays

PRODUCT IDENTIFICATION

SKSHC 0603 — 2R2 M

Product Code

Dimension：**L** × **W** × **H** (mm)
0402：4.6×4.0×2.0
0503：5.7×5.1×3.0
0603：7.2×6.6×3.0
0603L：7.2×6.6×3.0
0605：7.2×6.6×5.0
1004：11.6×10.1×4.0
1005：11.6×10.1×5.0
1204：13.8×12.6×4.0
1205：13.8×12.6×5.0
1265：13.8×12.6×6.5
1770：17.5×17.5×7.0

Inductance Deviation
M：±20%
N：±30%

Inductance Value
2R2：2.2μH
R47：0.47μH
100：10μH

SHAPE AND DIMENSIONS



RECOMMENDED PAD SIZE



Specification	Dimensions							
	A	B	Cmax	D	E	a Typ	b Typ	c Typ
SKSHC0402	4.6±0.3	4.0±0.3	2.0	2.0±0.3	0.8	2.5	2.5	5.2
SKSHC0503	5.7±0.3	5.1±0.3	3.0	2.1±0.3	1.2	2.5	2.2	6.5
SKSHC0603	7.2±0.4	6.6±0.3	3.0	3.0±0.3	1.6	3.5	3.7	8.5
SKSHC0603L	7.2±0.4	6.6±0.3	3.0	3.0±0.3	1.6	3.5	3.7	8.5
SKSHC0605	7.2±0.4	6.6±0.3	5.0	3.0±0.3	1.6	3.5	3.7	8.5
SKSHC1004	11.6max	10.1±0.3	4.0	3.0±0.3	2.5	3.5	5.4	13.0
SKSHC1005	11.6max	10.1±0.3	5.0	3.0±0.3	2.5	3.5	5.4	13.0
SKSHC1204	13.8max	12.6±0.3	4.0	3.5/3.0±0.5	2.7	5.0	6.5	14.5
SKSHC1205	13.8max	12.6±0.3	5.0	3.5/3.0±0.5	2.7	5.0	6.5	14.5
SKSHC1265	13.8max	12.6±0.3	6.5	3.5/3.0±0.5	2.7	5.0	6.5	14.5
SKSHC1770	17.5±1.0	17.5max	7.0	11.94±0.5	2.5	12.6	10.4	19.6

SPECIFICATIONS

SKSHC0402 TYPE

Part Number	Inductance	L Test Freq.	Max.DC Resistance	Temperature rise current	Saturation current
Units	μH	kHz/V	mΩ	A	A
Symbol	L	Freq	DCR	Irms	Isat
SKSHC0402-R22	0.22	100/1	6.6	9.0	12.5
SKSHC0402-R33	0.33	100/1	12.5	8.0	11.0
SKSHC0402-R47	0.47	100/1	14.0	7.0	10.0
SKSHC0402-R68	0.68	100/1	18.0	5.2	8.0
SKSHC0402-1R0	1.0	100/1	27.0	4.5	7.0
SKSHC0402-1R5	1.5	100/1	48.0	4.0	6.0
SKSHC0402-2R2	2.2	100/1	58.0	3.0	5.0
SKSHC0402-3R3	3.3	100/1	87.0	2.5	4.0
SKSHC0402-4R7	4.7	100/1	120.0	2.2	3.0
SKSHCO402-6R8	6.8	100/1	190.0	1.5	2.5
SKSHC0402-100	10.0	100/1	250.0	1.2	1.8

SKSHC0503 TYPE

Part Number	Inductance	L Test Freq.	Max.DC Resistance	Temperature rise current	Saturation current
Units	μH	kHz/V	mΩ	A	A
Symbol	L	Freq	DCR	Irms	Isat
SKSHC0503-R22	0.22	100/1	4.5	16.0	28.0
SKSHC0503-R33	0.33	100/1	7.0	14.0	18.0
SKSHC0503-R47	0.47	100/1	7.5	10.0	12.0
SKSHC0503-R68	0.68	100/1	12.0	8.0	12.0
SKSHC0503-1R0	1.0	100/1	15.0	7.0	9.0
SKSHC0503-1R2	1.2	100/1	15.0	6.5	8.8
SKSHC0503-1R5	1.5	100/1	25.0	6.0	8.5
SKSHC0503-2R2	2.2	100/1	29.0	5.5	8.0
SKSHC0503-3R3	3.3	100/1	38.0	4.5	6.0
SKSHC0503-4R7	4.7	100/1	60.0	4.0	5.0
SKSHC0503-6R8	6.8	100/1	86.0	3.5	4.5
SKSHC0503-8R2	8.2	100/1	105.0	3.3	4.0
SKSHC0503-100	10.0	100/1	126.0	2.5	3.5
SKSHC0503-150	15.0	100/1	190.0	1.8	2.2
SKSHC0503-220	22.0	100/1	260.0	1.3	1.9

SKSHC0603 TYPE

Part Number	Inductance	L Test Freq.	Max.DC Resistance	Temperature rise current	Saturation current
Units	μH	kHz/V	mΩ	A	A
Symbol	L	Freq	DCR	Irms	Isat
SKSHC0603-R22	0.22	100/1	3.0	23.0	34.0
SKSHC0603-R33	0.33	1000/1	3.5	21.0	25.0
SKSHC0603-R47	0.47	100/1	4.1	18.0	20.0
SKSHC0603-R68	0.68	100/1	5.9	16.0	17.0
SKSHC0603-R82	0.82	100/1	7.0	14.0	16.0
SKSHC0603-1R0	1.0	100/1	10.0	11.0	15.0
SKSHC0603-1R2	1.2	100/1	10.5	10.0	14.0
SKSHC0603-1R5	1.5	100/1	12.5	9.0	12.5

Part Number	Inductance	L Test Freq.	Max.DC Resistance	Temperature rise current	Saturation current
Units	μH	kHz/V	mΩ	A	A
Symbol	L	Freq	DCR	Irms	Isat
SKSHC0603-1R8	1.8	100/1	16.0	9.0	11.0
SKSHC0603-2R2	2.2	100/1	17.5	8.5	10.0
SKSHC0603-3R3	3.3	100/1	36.0	6.0	9.5
SKSHC0603-4R7	4.7	100/1	40.0	5.0	8.0
SKSHC0603-5R6	5.6	100/1	55.0	4.8	7.5
SKSHC0603-6R8	6.8	100/1	60.0	4.5	6.5
SKSHC0603-8R2	8.2	100/1	70.0	4.0	6.0
SKSHC0603-100	10.0	100/1	105.0	3.0	5.5
SKSHC0603-150	15.0	100/1	130.0	2.6	3.8
SKSHC0603-220	22.0	100/1	167.0	2.3	3.1
SKSHC0603-330	33.0	100/1	270.0	2.0	2.5
SKSHC0603-470	47.0	100/1	350.0	1.7	2.0

SKSHC0603L TYPE

Part Number	Inductance	L Test Freq.	Max.DC Resistance	Temperature rise current	Saturation current
Units	μH	kHz/V	mΩ	A	A
Symbol	L	Freq	DCR	Irms	Isat
SKSHC0603L-1R5M	1.5	100/1	12.1	9.5	12.0
SKSHC0603L-2R2M	2.2	100/1	15.0	9.0	10.0
SKSHC0603L-3R3M	3.3	100/1	22.0	6.5	9.5
SKSHC0603L-4R7M	4.7	100/1	33.0	5.5	8.0
SKSHC0603L-5R6M	5.6	100/1	42.0	5.0	6.5
SKSHC0603L-6R8M	6.8	100/1	48.0	4.5	6.0
SKSHC0603L-8R2M	8.2	100/1	60.0	4.0	6.0
SKSHC0603L-100M	10.0	100/1	68.0	3.5	5.5
SKSHC0603L-150M	15.0	100/1	113.0	2.5	4.0

SKSHC0605 TYPE

Part Number	Inductance	L Test Freq.	Max.DC Resistance	Temperature rise current	Saturation current
Units	μH	kHz/V	mΩ	A	A
Symbol	L	Freq	DCR	Irms	Isat
SKSHC0605-1R0	1.0	100/1	6.5	12.0	13.0
SKSHC0605-1R5	1.5	100/1	8.5	10.0	12.0
SKSHC0605-2R2	2.2	100/1	13.5	7.0	10.0
SKSHC0605-3R3	3.3	100/1	22.0	6.5	9.0
SKSHC0605-4R7	4.7	100/1	30.0	5.7	8.0
SKSHC0605-6R8	6.8	100/1	44.0	5.0	7.0
SKSHC0605-100	10.0	100/1	55.0	4.5	6.0
SKSHC0605-150	15.0	100/1	85.0	3.5	4.0
SKSHC0605-220	22.0	100/1	130.0	2.8	3.5
SKSHC0605-330	33.0	100/1	180.0	2.4	3.0
SKSHC0605-470	47.0	100/1	290.0	2.0	2.5
SKSHC0605-680	68.0	100/1	468.0	1.2	2.0

SKSHC1004 TYPE

Part Number	Inductance	L Test Freq.	Max.DC Resistance	Temperature rise current	Saturation current
Units	μH	kHz/V	mΩ	A	A
Symbol	L	Freq	DCR	Irms	Isat
SKSHC1004-R36	0.36	100/1	1.2	34	42
SKSHC1004-R47	0.47	100/1	1.68	28	38
SKSHC1004-R56	0.56	100/1	1.8	27	32
SKSHC1004-R68	0.68	100/1	2.4	23	30
SKSHC1004-R82	0.82	100/1	3.0	20	26
SKSHC1004-1R0	1.0	100/1	3.3	20	26
SKSHC1004-1R5	1.5	100/1	4.2	16	22
SKSHC1004-2R2	2.2	100/1	7.0	14	16
SKSHC1004-3R3	3.3	100/1	11.8	11	13
SKSHC1004-4R7	4.7	100/1	16.5	8.5	12
SKSHC1004-5R6	5.6	100/1	18.0	8.2	11
SKSHC1004-6R8	6.8	100/1	25.0	8	10

Part Number	Inductance	L Test Freq.	Max.DC Resistance	Temperature rise current	Saturation current
Units	μH	kHz/V	mΩ	A	A
Symbol	L	Freq	DCR	Irms	Isat
SKSHC1004-8R2	8.2	100/1	27.0	7.5	9
SKSHC1004-100	10	100/1	30.0	6.5	7
SKSHC1004-150	15	100/1	45.0	6.3	6
SKSHC1004-220	22	100/1	66.0	5	5.5
SKSHC1004-330	33	100/1	92.0	4	4.5
SKSHC1004-470	47	100/1	150.0	3	4
SKSHC1004-680	68	100/1	205.0	2.3	3

SKSHC1005 TYPE

Part Number	Inductance	L Test Freq.	Max.DC Resistance	Temperature rise current	Saturation current
Units	μH	kHz/V	mΩ	A	A
Symbol	L	Freq	DCR	Irms	Isat
SKSHC1005-1R0	1.0	100/1	3.0	19.0	28
SKSHC1005-1R5	1.5	100/1	4.0	16.0	21
SKSHC1005-1R8	1.8	100/1	5.0	15.0	20
SKSHC1005-2R2	2.2	100/1	6.6	13.0	19
SKSHC1005-3R3	3.3	100/1	11.0	11.0	18
SKSHC1005-4R7	4.7	100/1	15.0	10.0	15
SKSHC1005-5R6	5.6	100/1	18.0	8.5	14
SKSHC1005-6R8	6.8	100/1	19.2	8.0	13
SKSHC1005-100	10.0	100/1	28.0	7.0	10
SKSHC1005-150	15.0	100/1	42.0	6.5	7
SKSHC1005-220	22.0	100/1	66.0	5.5	6
SKSHC1005-330	33.0	100/1	84.0	4.5	5
SKSHC1005-470	47.0	100/1	150.0	3.0	4.5
SKSHC1005-680	68.0	100/1	205.0	2.5	3.5

SKSHC1204 TYPE

Part Number	Inductance	L Test Freq.	Max.DC Resistance	Temperature rise current	Saturation current
Units	μH	kHz/V	mΩ	A	A
Symbol	L	Freq	DCR	Irms	Isat
SKSHC1204-R47	0.47	100/1	2.0	29.0	38.4
SKSHC1204-R68	0.68	100/1	3.5	24.0	37.6
SKSHC1204-R82	0.82	100/1	4.5	24.0	32
SKSHC1204-1R0	1.0	100/1	7.5	20.0	28
SKSHC1204-1R5	1.5	100/1	9.5	17.0	24.4
SKSHC1204-2R2	2.2	100/1	11.5	15.0	20.8
SKSHC1204-3R3	3.3	100/1	13.0	13.0	16.8
SKSHC1204-4R7	4.7	100/1	14.5	11.0	14.4
SKSHC1204-6R8	6.8	100/1	20.0	8.0	11.2
SKSHC1204-100	10.0	100/1	25.0	7.0	8
SKSHC1204-150	15.0	100/1	39.0	5.8	6
SKSHC1204-220	22.0	100/1	51.0	3.8	4.8

SKSHC1205 TYPE

Part Number	Inductance	L Test Freq.	Max.DC Resistance	Temperature rise current	Saturation current
Units	μH	kHz/V	mΩ	A	A
Symbol	L	Freq	DCR	Irms	Isat
SKSHC1205-R33	0.33	100/1	0.9	46.0	62
SKSHC1205-R36	0.36	100/1	1.1	41.0	60
SKSHC1205-R47	0.47	100/1	1.3	37.0	46
SKSHC1205-1R0	1.0	100/1	2.5	29.0	37
SKSHC1205-1R5	1.5	100/1	4.1	23.0	30
SKSHC1205-1R8	1.8	100/1	4.5	18.0	26
SKSHC1205-2R2	2.2	100/1	5.0	15.0	25
SKSHC1205-3R3	3.3	100/1	9.0	12.0	20
SKSHC1205-4R7	4.7	100/1	11.5	11.0	16
SKSHC1205-5R6	56	100/1	15.0	10.5	15
SKSHC1205-6R8	6.8	100/1	22.0	9.0	14

Part Number	Inductance	L Test Freq.	Max.DC Resistance	Temperature rise current	Saturation current
Units	μH	kHz/V	mΩ	A	A
Symbol	L	Freq	DCR	Irms	Isat
SKSHC1205-8R2	8.2	100/1	24.0	8.5	13
SKSHC1205-100	10.0	100/1	29.0	7.5	11.0
SKSHC1205-150	15.0	100/1	32.0	6.0	9.0
SKSHC1205-220	22.0	100/1	50.0	5.0	7.0
SKSHC1205-330	33.0	100/1	84.0	3.5	6.0
SKSHC1205-470	47.0	100/1	130.0	3.0	5.0

SKSHC1265 TYPE

Part Number	Inductance	L Test Freq.	Max.DC Resistance	Temperature rise current	Saturation current
Units	μH	kHz/V	mΩ	A	A
Symbol	L	Freq	DCR	Irms	Isat
SKSHC1265-4R7	4.7	100/1	8.5	16	24
SKSHC1265-5R6	5.6	100/1	10.5	14	22.5
SKSHC1265-6R8	6.8	100/1	12.0	13	19
SKSHC1265-8R2	8.2	100/1	14.0	12	16
SKSHC1265-100	10.0	100/1	16.5	11	15
SKSHC1265-150	15.0	100/1	26.0	9.5	11
SKSHC1265-220	22.0	100/1	36.0	8	9
SKSHC1265-330	33.0	100/1	65.0	6.5	8
SKSHC1265-470	47.0	100/1	70.0	5.5	6.8

SKSHC1770 TYPE

Part Number	Inductance	L Test Freq.	Max.DC Resistance	Temperature rise current	Saturation current
Units	μH	kHz/V	mΩ	A	A
Symbol	L	Freq	DCR	Irms	Isat
SKSHC1770-1R0	1.0	100/1	1.9	32	55.5
SKSHC1770-1R5	1.5	100/1	2.8	23	40.0
SKSHC1770-2R2	2.2	100/1	3.0	18	40.0
SKSHC1770-3R3	3.3	100/1	3.2	15	35.0
SKSHC1770-4R7	4.7	100/1	5.8	13	30.0
SKSHC1770-6R8	6.8	100/1	8.0	10.5	22.5
SKSHC1770-8R2	8.2	100/1	13.0	9.5	20.0
SKSHC1770-100	10	100/1	13.0	9.5	19.0
SKSHC1770-150	15	100/1	22.0	9	14.0
SKSHC1770-220	22	100/1	26.0	8.5	12.0
SKSHC1770-330	33	100/1	38.5	8	10.7
SKSHC1770-470	47	100/1	53.0	6	8.7
SKSHC1770-560	56	100/1	60.5	5.2	7.2
SKSHC1770-680	68	100/1	79.0	4.5	6.1
SKSHC1770-101	100.0	100/1	123.0	4	5.0
SKSHC1770-680	68	100/1	79.0	4.5	6.1
SKSHC1770-101	100.0	100/1	123.0	4	5.0

TYPICAL ELECTRICAL CHARACTERISTICS

SKSHC0402 TYPE





SKSHC0503 TYPE



SKSHC0603 TYPE





SKSHC0605 TYPE





SKSHC1004 TYPE



SKSHC1005 TYPE





SKSHC1204 TYPE





SKSHC1205 TYPE

Inductance VS Current



Temperature VS Current



SKSHC1265 TYPE

Inductance VS Current



Temperature VS Current



SKSHC1770 TYPE

Inductance VS Current



Inductance VS Current