



Unidirectional TVS Diode Array

Description


The SMxx Series is designed for applications requiring transient overvoltage protection capability. They are intended for use in voltage and ESD sensitive equipment such as computers, printers, business machines, communication systems, medical equipment and other applications. These devices are ideal for situations where board space is at a premium.

This series has been specifically designed to protect sensitive components which are connected to power data and transmission lines from overvoltage caused by ESD(electrostatic discharge), CDE (Cable Discharge Events),and EFT (electrical fast transients).

Ordering Information

- Device:SMxx
- Package:SOT-23
- Material:Halogen free and RoHS compliant
- Packing:Tape & Reel
- Quantity per reel:3000pcs

Pin Configuration



Features

- IEC61000-4-2(ESD) $\pm 30\text{kV}(\text{air})$
 $\pm 30\text{kV}(\text{contact})$
- IEC61000-4-4(EFT) 40A (5/50ns)
- Peak power dissipation: 450W($t_p=8/20\mu\text{s}$)
- Protects two unidirectional lines
- Low clamping voltage
- Working voltage: 3.3V to 36V
- Low leakage current


Mechanical Data

- SOT-23 package
- Flammability rating: UL 94V-0
- Packaging: Tape and Reel
- High temperature soldering guaranteed: 260°C/10s
- Reel size: 7 inch
- MSL 1

Applications

- Cell Phone Handsets and Accessories
- Microprocessor based equipment
- Personal Digital Assistants(PDA's)
- Notebooks, Desktops, and Servers
- Portable Instrumentation
- Networking and Telecom
- Serial and Parallel Ports
- Peripherals

Package Outline





SM03 THUR SM36

Absolute Maximum Rating

Parameter	Symbol	Value	Units
ESD per IEC 61000-4-2(Air)	V_{ESD}	± 30	kV
ESD per IEC 61000-4-2(Contact)		± 30	
Peak Pulse Power(8/20 μ s)	P_{PP}	450	W
Operating Temperature	T_{OPT}	-55~+150	°C
Storage Temperature	T_{STG}	-55~+150	°C
Lead Soldering Temperature	T_L	260(10 sec.)	°C

Electrical Characteristics ($T_A=25^{\circ}\text{C}$)

Part Number	Device Marking	V_{RWM} (V) (max.)	V_B (V) (min.)	I_T (mA)	$V_{C@1A}$ (V) (max.)	V_C (V) (max.) (@A)		I_R (μ A) (max.)	C_J (pF) (max.)
SM03	M03	3.3	4.0	1	7.5	16.0	25	40	400
SM05	M05	5.0	6.0	1	9.8	18.0	24	10	200
SM08	M08	8.0	8.5	1	13.4	24.0	20	2	180
SM12	M12	12.0	13.3	1	19.0	32.0	17	1	100
SM15	M15	15.0	16.7	1	24.0	38.0	13	1	80
SM18	M18	18.0	20.0	1	29.0	45.0	10	1	70
SM20	M20	20.0	22.3	1	35.0	50.0	9	1	52
SM24	M24	24.0	26.7	1	43.0	52.0	9	1	50
SM36	M36	36.0	40.0	1	60.0	75.0	6	1	35



SM03 THUR SM36

Electrical Characteristics Curve

Fig1. 8/20us Pulse Waveform




Fig2. Contact Discharge Current Waveform (IEC 61000-4-2)




Fig3 Voltage vs Capacitance




Fig4 Voltage vs Capacitance




Fig5 Clamping Voltage vs Peak Pulse Current





Fig6 Clamping Voltage vs Peak Pulse Current






SM03 THUR SM36

Package Information

SOT-23

Dimensions in mm



Symbol	Dimensions In Millimeters			Dimensions In Inches		
	Min	Nom	Max	Min	Nom	Max
A	0.89	1.00	1.11	0.035	0.040	0.044
A1	0.01	0.06	0.10	0.001	0.002	0.004
b	0.37	0.44	0.50	0.015	0.018	0.020
c	0.09	0.13	0.18	0.003	0.005	0.007
D	2.80	2.90	3.04	0.110	0.114	0.120
E	1.20	1.30	1.40	0.047	0.051	0.055
e	1.78	1.90	2.04	0.070	0.075	0.081
L	0.35	0.54	0.69	0.014	0.021	0.029
HE	2.10	2.40	2.64	0.083	0.094	0.104



Shikues Disclaimer

1.Accuracy of Information and Right to Modify

The information provided in this document is for reference only. Shikues reserves the right to make changes to this document and to the specifications of the products described herein at any time, without prior notice, for the purpose of improving reliability, function, design, or for any other reason. It is the customer's responsibility to obtain and verify the latest product information and specifications before making any final design, procurement, or usage decisions.

2.No Warranty

Shikues makes no express or implied warranties, representations, or guarantees regarding the suitability of its products for any particular purpose.

Shikues assumes no liability for any assistance provided or for the design of customer products. All products are supplied "as is."

3.Intended Use and Limitation of Liability

The products described in this document are intended for use in general-purpose electronic devices. They are neither designed nor tested nor authorized for use in transportation equipment or applications requiring high reliability. Unless expressly authorized in writing by Shikues, these products must not be used as critical components in life-support systems or any applications where failure could directly pose a risk to human life (including, but not limited to, medical devices, transportation systems, aerospace equipment, nuclear facilities, and safety-critical systems).

Shikues assumes no responsibility or liability for any consequences arising from the use of its products in unauthorized or unintended applications.

Neither Shikues nor its representatives shall be held liable for any resulting damages.

4.Intellectual Property

This document does not grant any express or implied license—whether by estoppel, implication, or otherwise—to use any intellectual property rights of Shikues.